

In this month's Hydrafile:**News:** - Hyspecs confirms full line product access from Eaton ...**Products of interest:** - The *NEW* Char-Lynn 'T' Series Brake motor ...**Subscriber feedback:** - If you don't see what you need - contact us ...**News:****Effective immediately** Hyspecs has full line access of the Eaton Hydraulic product range.

Hyspecs has been a dedicated national agent for the Eaton line of hydraulic product for the last 12 years. During this time Hyspecs has maintained a large stock of Char-Lynn Motors, Piston Pumps and Motors and Light, Medium and Heavy Duty Transmission products. To support these products Hyspecs also kept an extensive range of spare parts and kits in stock to allow for product conversions and breakages.

In 1999, the Eaton Corporation acquired the Vickers Corporation. This international transaction created major changes in the New Zealand hydraulics market. It meant that all Vickers distributors of the time gained access to Eaton product for which Hyspecs had previous sole responsibility. In response to this development, Hyspecs has grown its sales volume of Eaton products by finding new market sectors and customers.

Over the last 4 years, Hyspecs' commitment and service of the Eaton product range has been unparalleled in the New Zealand market. In recognition of this commitment, Eaton Corporation has offered Hyspecs the complete Vickers line of hydraulic product to allow Hyspecs to become a full line agent. Hyspecs sees this opportunity as an enhancement to the existing mix of product. A stocking policy is being developed, and over the next 6 months the stocked range will increase to significant levels.

Contact Hyspecs today for pricing and availability of Eaton - Vickers product. Click here to send your query to Hyspecs - [Hyspecs Information](#)

Products of interest:**Eaton Char-Lynn** have released a new brake motor using the LSHT 'T' Series motor frame.

Features include:

- Rear mounted integral brake with 6:1 torque advantage
- Spring applied pressure release wet brake
- Load hold capacity is tailored to match motor configuration
- Access port for manual brake release for emergency situations
- Can be supplied with optional counterbalance valve in single assembly



- Displacements from 36 to 370 cc/rev
- Max. operating pressure - 155 bar (depending on displacement)
- Max. continuous input flow - 57 lpm (depending on displacement)
- Max. continuous torque - 440 Nm (depending on displacement)

For more information including detailed specifications, pricing and availability, contact Hyspecs by clicking [Hyspecs Information](#)

Subscriber feedback:

The Hydrafile's goal is to provide you with a valid source of information showcasing what is new at Hyspecs, as well as providing samples of existing product lines. Even if the products contained in this email do not fit in with your current requirements, please do not hesitate to contact us. You never know, we may have a solution in stock, or an idea that could help.

Contacting us is easy:

1. Click anywhere you see [Hyspecs Information](#) and your email program will open ready to go.
2. Call one of our Sales Engineers on the numbers listed above
3. Click on our website address listed above and go to our contact page

Thank you for your interest and until next month

Kim Clarke
National Marketing Manager
kim@hyspecs.co.nz

